

<b>TOLERÂNCIA DIMENSIONAL PARA BARRAS DE AÇO</b>							
<b>Dimensão Nominal (mm)</b>		<b>Tolerância (mm)</b>					
<b>Maior que</b>	<b>Até</b>	<b>ISO h7</b>	<b>ISO h8</b>	<b>ISO h9</b>	<b>ISO h10</b>	<b>ISO h11</b>	<b>ISO h12</b>
<b>1</b>	<b>3</b>	<b>-0.009</b>	<b>-0.014</b>	<b>-0.025</b>	<b>-0.040</b>	<b>-0.060</b>	<b>-0.090</b>
<b>3</b>	<b>6</b>	<b>-0.012</b>	<b>-0.018</b>	<b>-0.030</b>	<b>-0.048</b>	<b>-0.075</b>	<b>-0.120</b>
<b>6</b>	<b>10</b>	<b>-0.015</b>	<b>-0.022</b>	<b>-0.036</b>	<b>-0.058</b>	<b>-0.090</b>	<b>-0.150</b>
<b>10</b>	<b>18</b>	<b>-0.018</b>	<b>-0.027</b>	<b>-0.043</b>	<b>-0.070</b>	<b>-0.110</b>	<b>-0.180</b>
<b>18</b>	<b>30</b>	<b>-0.021</b>	<b>-0.033</b>	<b>-0.052</b>	<b>-0.084</b>	<b>-0.130</b>	<b>-0.210</b>
<b>30</b>	<b>50</b>	<b>-0.025</b>	<b>-0.039</b>	<b>-0.062</b>	<b>-0.100</b>	<b>-0.160</b>	<b>-0.250</b>
<b>50</b>	<b>80</b>	<b>-0.030</b>	<b>-0.046</b>	<b>-0.074</b>	<b>-0.120</b>	<b>-0.190</b>	<b>-0.300</b>
<b>80</b>	<b>120</b>	<b>-0.035</b>	<b>-0.054</b>	<b>-0.087</b>	<b>-0.140</b>	<b>-0.220</b>	<b>-0.350</b>
<b>120</b>	<b>180</b>	<b>-0.040</b>	<b>-0.063</b>	<b>-0.100</b>	<b>-0.160</b>	<b>-0.250</b>	<b>-0.400</b>
<b>180</b>	<b>250</b>	<b>-0.046</b>	<b>-0.072</b>	<b>-0.115</b>	<b>-0.185</b>	<b>-0.290</b>	<b>-0.460</b>